



SensorSAFE[™] infrared dispense option



SensorSAFE not recommended for use with clear containers or for applications in direct sunlight

Ice and water dispensers				
lce storage capacity	Dispense	lce machine cooling	Voltage V/Hz	Item number
	Lever	air	220/60	C25Cl425A-L
11.4 kg	Lever	air	230/50	E25CI425A-L
(25 lb)	SensorSAFE	air	220/60	C25Cl425A-S
	SensorSAFE	air	230/50	E25CI425A-S
	Lever	air	220/60	C50Cl425A-L
22.7 kg	Lever	air	230/50	E50CI425A-L
(50 lb)	SensorSAFE	air	220/60	C50CI425A-S
	SensorSAFE	air	230/50	E50CI425A-S

Ice-only available, add -I Example: E25CI425A-LI

Ice production				
Temperatures air/water	21/10 C (70/50 F)	32/21 C (90/70 F)		
Air-cooled	186.1 kg (410 lb)	140.7 kg (310 lb)		
Energy consumption per 45.4 kg (100 lb) ice	N/A	6.0 kWh air-cooled		
Water consumption	45.4 L (12.0 gal) of potable water per 45.4 kg (100 lb) of ice			

Symphony Plus[™] ice and water dispenser

C/E 25 & 50 CI series countertop with Chewblet® ice machine

Features

- 11.4 or 22.7 kg (25 or 50 lb) ice storage capacity
- Counter-height removable air-cooled ice machine with up to 186 kg (410 lb) daily production of popular Chewblet ice
 - modular ice machine slides out from behind lower front panel
 - soft, chewable, compressed nugget ice is preferred over cubes¹ and is ideal for patient care
- New Quiet Night[™] sleep mode turns off ice machine when idle Designed with sanitation in mind
- New automatic self-flushing of ice machine removes impurities
- New drain cup provides internal air gap for added protection of food zone components from drain line contaminants
 - Agion $^{\ensuremath{\text{\circ}}}$ silver-based antimicrobial provides protection of key ice and water contact components 2
 - one-hand lever or SensorSAFE infrared ice dispense
 - Dependable design, easy to service and clean
- New cleaning and sanitizing of entire machine takes only 1 hour
- New LED control board provides at-a-glance machine status
 - panels are easily removed for accessibility to all components
 - ice machine parts are common across all Symphony Plus dispensers
 - stainless steel evaporator and auger deliver long life
 - Environmentally responsible
 - R404a refrigerant has zero ozone depletion potential
 - continuous ice making process uses less electricity and water
 - Durable, attractive dispenser
 - frame and exterior cabinet are stainless steel with accent trim
 - poly drain pan, grille and dispenser lid are corrosion-resistant
 - secured top lid

Easy installation and industry's best warranty

- comes fully assembled and installs with three easy connections electric, water and drain
- warranty 3 years parts and labor, 5 years compressor parts³

Accessories

- Base stand with or without factory installed water filter (refer to form# 7010) 10.16 cm (4.00") leg kit (item# 00188417)
- Pressurized water sanitizing kits (refer to form# 6830)
- SafeCLEAN Plus[™], 3 x 7 oz packets (item# 01054683)
- Water filters (refer to form# 6380, 9905, 6070)
- Additional Symphony Plus accessories (refer to price list)

Follett Europe Polska Sp. z o.o. Mokry Dwór 26C 83-021 Wiślina, Poland +48 (58) 785-6140 | Fax: +48 (58) 785-6159 folletteurope.com

FOLLETT[®] Innovative solutions, inspired by ice

801 Church Lane | Easton, PA 18040, USA 1.610.252.7301 | Fax: +1.610.250.0696 | follettice.com

Specification

Ice storage capacity	25 Series – 11.4 kg (25 lb) 50 Series – 22.7 kg (50 lb)
W1 Width, dispenser	53.3 cm (21.00")
W2 Width, base stand accessory	57.8 cm (22.75")
D1 Depth, entire dispenser	61.0 cm (24.00")
D2 Depth, drain pan	17.78 cm (7.00")
D3 Depth, base stand accessory	61.9 cm (24.38")
H1 Height	25 Series – 91.4 cm (36.00") 50 Series – 101.6 cm (40.00")
H2 Dispense height clearance	26.7 cm (10.50")
H3 Height, base stand	83.8 cm (33.00")
Ventilation clearance	7.62 cm (3.00") all sides
Service clearance	30.5 cm (12.00") top, 15.24 cm (6.00") left side
Utility connection location	back or bottom
Utility connection location C1 220 V/60/1 ("C" models) / 230 V/50/1 ("E" models) electrical	, , , , , , , , , , , , , , , , , , ,
C1 220 V/60/1 ("C" models) / 230 V/50/1 ("E" models)	back or bottom 5.5 amps, 0.8 kW
C1 220 V/60/1 ("C" models) / 230 V/50/1 ("E" models) electrical	back or bottom 5.5 amps, 0.8 kW 2.4 m (8') cord only
C1 220 V/60/1 ("C" models) / 230 V/50/1 ("E" models) electrical C2 Potable water inlet	back or bottom 5.5 amps, 0.8 kW 2.4 m (8') cord only 3/8" FPT
C1 220 V/60/1 ("C" models) / 230 V/50/1 ("E" models) electrical C2 Potable water inlet C3 Drain	back or bottom 5.5 amps, 0.8 kW 2.4 m (8') cord only 3/8" FPT 3/4" MPT
C1 220 V/60/1 ("C" models) / 230 V/50/1 ("E" models) electrical C2 Potable water inlet C3 Drain Heat rejection	back or bottom 5.5 amps, 0.8 kW 2.4 m (8') cord only 3/8" FPT 3/4" MPT 5000 BTU/hr
C1 220 V/60/1 ("C" models) / 230 V/50/1 ("E" models) electrical C2 Potable water inlet C3 Drain Heat rejection Air temperature	back or bottom 5.5 amps, 0.8 kW 2.4 m (8') cord only 3/8" FPT 3/4" MPT 5000 BTU/hr 10 - 38 C (50 - 100 F)
C1 220 V/60/1 ("C" models) / 230 V/50/1 ("E" models) electrical C2 Potable water inlet C3 Drain Heat rejection Air temperature Water temperature	back or bottom 5.5 amps, 0.8 kW 2.4 m (8') cord only 3/8" FPT 3/4" MPT 5000 BTU/hr 10 - 38 C (50 - 100 F) 7 - 32 C (45 - 90 F)
C1 220 V/60/1 ("C" models) / 230 V/50/1 ("E" models) electrical C2 Potable water inlet C3 Drain Heat rejection Air temperature Water temperature Potable water pressure	back or bottom 5.5 amps, 0.8 kW 2.4 m (8') cord only 3/8" FPT 3/4" MPT 5000 BTU/hr 10 - 38 C (50 - 100 F) 7 - 32 C (45 - 90 F) 69 - 483 kpa (10 - 70 psi)

SHORT FORM SPECIFICATION: (Choose one) ____ Ice and water or ____ ice-only dispenser to be Follett® automatic load in countertop configuration, with _ 11.4 kg (25 lb) or ____ 22.7 kg (50 lb) of storage. Environmentally responsible R404a ice machine removable for cleaning and maintenance. Dispenser frame and cabinet stainless steel with plastic trim. Ice machine to produce approximately 186 kg (410 lb) of Chewblet compressed nugget ice at air temperature of 21 C (70 F), water temperature of 10 C (50 F). Ice machine equipped with automatic self-flushing and Quiet Night sleep mode. Dispenser to have automatic bin level control to start and stop ice machine. Storage area insulated with non-CFC, high density, foamed-in-place polyurethane. 2.4 m (8') cord only. 230 V dispensers CE listed.

H1 D2 H2 air intake BS* H3 D3 W2 c 0 C1 C2 C3 Ô 2.24 cm _ 3.50 cm (1.38") (0.88") 6.50 cm (2.56")

Dimensional drawing D1

W1

BS*- Base stand sold separately; measurements shown are with base stand legs at lowest position.

- See dispenser detail sheet, form# 6675, for counter cut outs.
- 1 Independent third party studies. Contact Follett for details.
- 2 Disclaimer: Antimicrobial protection is limited to the treated components and does not treat water or ice.

26.67 cm (10.50")

- 3 Refer to price list for additional warranty information. Agion is a registered trademark of Sciessent LLC.
- Symphony Plus, SensorSAFE, SafeCLEAN and Quiet Night are trademarks of Follett LLC.
- Chewblet and Follett are registered trademarks of Follett LLC, registered in the US.

Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.

Follett Europe Polska Sp. z o.o. Mokry Dwór 26C 83-021 Wiślina, Poland +48 (58) 785-6140 | Fax: +48 (58) 785-6159 folletteurope.com

801 Church Lane | Easton, PA 18040, USA 1.610.252.7301 | Fax: +1.610.250.0696 | follettice.com Innovative solutions, inspired by ice



Form #7090 04/17 © Follett LLC

C/E 25/50 CI series countertop

