

# CDPSJ 200 Filter System

The CDPSJ filter system from Coast Distributors is designed to filter water in high flow rate / high volume applications. The system utilizes a high capacity 2 high 20" jumbo filter housing. Inlet and outlet connections are 3/4" bspm for easy connection to existing pipework or braided SS hoses. The housing features a vent button to assist in air bleeding and a downstream pressure gauge to measure water pressure and filter life. The high capacity Fibron® filter cartridge provided with the system reduces sediment, chlorine, taste & odour. A mounting bracket and handy housing sump spanner are also included with the CDPSJ system.



### Features & Benefits

- Reduces sediment, dirt, rust, chlorine, taste & odour
- High capacity 2 high system
- Pressure Gauge – to measure downstream water pressure
- Vent – to relieve pressure and vent air when changing the filter cartridge
- Utilises high capacity Fibron® cartridges for optimum performance and life

### Application

- Filters water to large commercial ice machines

Model	Description	Specifications
CDPSJ200	2 high housing incl. CDFB5W20 cartridge	W 220mm   H 720mm
CDFB5W20	Replacement cartridge 5 micron Fibron®	W 100mm   H 500mm

### Specifications and operating conditions

- Micron Rating: 5 micron nominal
- Flow Rate: < 30 lpm
- Water Pressure range: 200 – 860 kPa  
(Use pressure limiting valve if pressure is >860 kPa)
- Temperature range: 5 - 40° c
- Capacity: change-out filter cartridge every 6 months or on service cycle
- Inlet/outlet: 3/4 bspm