



## Model:

□ CIMO435



# Features and Benefits

- 30" (768 mm) wide space-saving design.
- · Produces up to 209kg of ice per day.
- · Energy and Environment
  - Exceeds new 2018 DOE (Department of Energy) regulations.
  - Up to 20% more energy efficient than other models.
  - Environmentally friendly, including BPA-free plastic and recyclable
- Sanitation
  - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
  - Built in Agion® ensures unbeatable antimicrobial protection.
  - Smart LED light indicates machine status and when cleaning is required.
  - Simple, one-touch controls for sanitization and descaling.
  - BPA-free snap-in, snap-out dishwasher-safe components.
- · Unique Dual Exhaust Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- $\mathit{Universal}$   $\mathit{Smart}$   $\mathit{Harness}^{\mathsf{TM}}$   $\mathit{control}$  board  $\mathit{simplifies}$  installation and servicing with better access, digital diagnostics, universal components and common configuration.

### Ice Form

### Bin Chart Kits for Combining Wider Bins with Smaller Models

FULL CUBE DIMENSIONS							
W x D x H (mm)	22 x 22 x 22						
HALF CUBE DIMENSIONS							
W x D x H (mm)	10 x 22 x 22						

	ICE STORAGE BINS								
	Model No. Capacity Width	<b>B25</b> 110 kg 762 mm	<b>B40</b> 156 kg 762 mm	<b>B42</b> 160 kg 559 mm	<b>B55</b> 232 kg 762 mm	ICB230SC 232 kg 764mm	ICB460 460 kg 1,226 mm	<b>B110</b> 388 kg 1,219 mm	
Kits	CIM0435	Kit Not Required		N/A	Kit Not Required		ВТ100	BPF-1	



CUBE

### **Options & Accessories**

WATER FILTERS						
Ice Machine Model	Manifold					
ree Pidelille Piddel	System	Replacement				
CIMo435	CD20B	CD200B				

Note: All modular cube CIM units can be installed with the O<sub>₹</sub>-Matic<sup>™</sup> Ozone Delivery System.

# Ice Maker Warranty

COMMERCIAL WARRANTY						
Ice Maker	3 YEARS parts and labor					
Evaporator and Compressor	<b>5 YEARS</b> parts					
























# COAST ICE & COLD SOLUTIONS


### Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust. Top louvers must not be blocked more than 75%.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".

#### **Dual Exhaust for Installation Flexibility**





Air Cooled

# **Operating Requirements**

MINIMUM	MAXIMUM
	50Hz
10°C	·- ° C
4.4°C	43°C
1.4 BAR	5.5 BAR
	10°C 4.4°C

## **Dimensions**

ALL MODELS						
W x D x H (mm)	768 x 616 x 540					

## **Specifications**

		Half-Cube Ice Production per 24hrs		<b>Water Usage</b> litres per 45 kg of Ice 32°c air/21°c water		kWH Used	Watts Used				
Model Number	Cond. Unit	21°c air/ 10°c water (kg)	32°c air/ 21°c water (kg)	Potable	Condenser			Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Approx. BTUs per hour
CIM0435A	Air	209	161	20.0	-	597	890	220-240/50/1	8.7	16	5,100

<sup>\*</sup> Daily ice production based on half cube configuration.

Notes: Number of Wires: Approx. Shipping Weight kg: Refrigerant Type:

3 (including ground) CIMO435A 70.3 R4O4A