



Model:

□ CIM1135




Features and Benefits

- · 30.25" (768 mm) wide space-saving design.
- · Produces up to 425kg of ice per day.
- Energy and Environment
 - Exceeds new 2018 DOE (Department of Energy) regulations.
 - Up to 20% more energy efficient than other models.
 - Environmentally friendly, including BPA-free plastic and recyclable parts.
- Sanitation
 - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
 - Built in Agion® ensures unbeatable antimicrobial protection.
 - Smart LED light indicates machine status and when cleaning is required.
 - Simple, one-touch controls for sanitization and descaling.
 - BPA-free snap-in, snap-out dishwasher-safe components.
- · Unique Dual Exhaust Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- Universal Smart Harness[™] control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

Ice Form

Bin Chart Kits for Combining Wider Bins with Smaller Models





CUBE

	ICE STORAGE BINS									
	Model No. Capacity Width	B25 110 kg 762 mm	B40 B42 156 kg 160 kg 762 mm 559 mm		B55 232 kg 762 mm	ICB230SC 232 kg 764 mm	ICB460 460 kg 1,226 mm	B110 388 kg 1,219 mm		
Kits	CIM1135	Kit Not Required		N/A	Kit Not Required		BT460	BPF-1		

Options & Accessories

WATER FILTERS							
Ice Machine Model	Manifold						
	System	Replacement					
CIM1135	CD20B	CD200B					

Note: All modular cube CIM units can be installed with the O_₹-Matic[™] Ozone Delivery System.

Ice Maker Warranty

COMMERCIAL WARRANTY						
Ice Maker	3 YEARS parts and labor					
Evaporator and Compressor	5 YEARS parts					






















Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".



Dual Exhaust for Installation Flexibility



Operating Requirements

50Hz	
o°C	
4° ℃	
BAR 5.5 BAR	
4	°C 43°C

Dimensions

ALL MODELS							
W x D x H (mm)	768 x 616 x 683						

Specifications

			Cube duction 24hrs	Water Usage litres per 45 kg of Ice 32°c air∕21°c water		kWH Used	Watts Used				
Model Number	Cond. Unit	21°c air/ 10°c water (kg)		Potable	Condenser	per 45 kg of ice @ 32°c air/ 21°c water		Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Approx. BTUs per hour
CIM1135A	Air	425	374	68	-	52	1791	220-240/50/1	15.2	25	19,300

^{*} Daily ice production based on half cube configuration.

Notes: Number of Wires: Approx. Shipping Weight kg: Refrigerant Type:

CIM1135: 3 (including ground) CIM1135A 105 R4O4A