



CIM1545 ON B110

## Features

- Space-saving 681 mm (26.8") tall design.
- Produces up to 728 kg of ice per day.
- *Harvest Assist* provides consistent ice production for the life of the ice maker while reducing energy consumption and increasing capacity.
- *Pure Ice*® exclusively by Ice-O-Matic. Built-in antimicrobial protection for the life of the ice maker inhibits bacteria growth on ice maker surfaces. Ice-O-Matic's optional water filtration system provides protection against unpleasant tastes, odors and scale formation.
- Durable, electroless nickel plating on all evaporator plates ensures reliability.
- Constructed from corrosion-resistant aluminum and fingerprint-proof plastic.

## Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIM1545	CD2oB	CD2ooB

## Ice Maker Warranty

Every Ice-O-Matic ice maker is backed by a warranty that provides both parts and labor coverage.

- Three years **Parts** and **Labor**.
- Five years **Parts** coverage on the evaporator and compressor.

## Ice Form



### CUBE

FULL CUBE DIMENSIONS	
W x D x H (mm)	22 x 22 x 22
W x D x H (in.)	7/8 x 7/8 x 7/8
HALF CUBE DIMENSIONS	
W x D x H (mm)	10 x 22 x 22
W x D x H (in.)	3/8 x 7/8 x 7/8

## Bin Chart *Kits for Combining Wider Bins with Smaller Models*

ICE STORAGE BINS								
Kits	Model No.	B25	B40	B42	B55	ICB23oSC	B110	ICB46o
	Capacity	110 kg	156 kg	160 kg	232 kg	232 kg	388 kg	460 kg
	Width	762 mm	762 mm	559 mm	762 mm	764 mm	1,219 mm	1,226 mm
CIM1545		N/A					Kit Not Required	Kit Not Required



Nature's antimicrobial



# ELEVATION SERIES CUBE ICE MAKER CIM1545



CIM1545 CUBE ICE MAKER

## Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust.

- A. Ice maker potable water in, 10 mm FPT.
- B. Ice maker water out, 20 mm FPT.
- C. Hole for electrical connections, 22 mm.
- D. Electrical junction box.

Dual Exhaust for Installation Flexibility



Air Cooled

## Operating Requirements

	MINIMUM	MAXIMUM
	<b>50Hz</b>	
Ambient Temp. Range Air	10 °C	43 °C
Water Temp.	4.4 °C	
Water Pressure	1.4 BAR	4.1 BAR

## Dimensions

ALL MODELS	
W x D x H (mm)	1,226 x 616 x 660

## Specifications

Model Number	Cond. Unit	Ice Production per 24hrs		Water Usage gallons per 45 kg of Ice 32°C air/21°C water		kWH Used per 45 kg of Ice @ 32°C air/ 21°C water	Watts Used per Hr Ice @ 32°C air/ 21°C water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Approx. BTUs per hour
		21°C air/ 10°C water kg	32°C air/ 21°C water kg	Potable	Condenser						
CIM1545A	Air	708	549	14.4	N/A	4.4	2,200	220-240/50/1	18.8	25/30	20,300

\* Daily ice production based on half cube configuration.

Number of Wires: 3 (including ground)  
Approx. Shipping Weight kg: CIM1545A 310

**REFRIGERANT:** R404A