FRANKE FOODSERVICE SOLUTIONS

EcO₃lce

ANTIMICROBIAL ICE PROTECTION







MODEL NUMBER

 $\square X_4$

PRODUCT OVERVIEW

The compact EcO₃Ice device uses a unique, synthetic diamond-based technology that continuously treats incoming ingredient water used by ice machines, killing bacteria, yeast and mold in the ice-making path from beginning to end. Reduces biofilm build-up, greatly extending required time between cleanings. With each cycle, EcO₃ ce creates a small, safe but effective amount of pure ozone-nature's own sanitizer-which continuously treats the machine interior, storage bin, remote bin and drains.

STANDARD PRODUCT FEATURES

- Attaches quickly and easily to incoming water line of ice machine
- Runs silently and automatically.
- Operator-replaceable, "twist-on" electrolytic cartridge.

X4 COMPATABILITY

- Suitable for all IOM Cube Ice Machines.
- Fits most commercial ice machines with ice making capacity of 45kgs or larger with flow rate of up to 4.9lpm.

CARTRIDGE LIFE

- Approximately 189,000 litres*.
- LED indicator lamps show status, tells when it's time to replace cartridge.

WARRANTY

- Warranted against defects in materials and workmanship for 1 year
 - Parts only, on head unit.
 - 30 days parts-only on cartridge.
 - Normal use exclusions apply, per Operation Manual.
 - Cartridge life is dependent upon water quality and ice machine water consumption.




















Coast Distributors PO Box 288 Unanderra NSW 2526 Ph: 1800 688 590 www.coastdistributors.com.au



Model X₄







SIDE VIEW

PLAN VIEW

DIMENSIONS	Width	97mm	
	Depth	91mm	
	Height	203mm	
CTRICAL	Voltage	100-240	Ì
	Phase	1	
	Amps (by phase)	1.25 Max	ľ
EC	Watts (by phase)	30 Max	l
⊞	Unswitched Circuit	Within 127mm of X4	
WEIGHT	Net Weight	0.82kgs	
	Gross Weight	0.91kgs	

SHORT-FORM SPECIFICATIONS: Model No EcO₃/ce X4 measures approximately 97mm W x 91mm D x 203mm H and requires 100-240v, 50/60 Hz supply for provided 24v, 1.25a transformer (integrated into power cord). Unit shall include synthetic diamond-based electrolytic technology to produce a small, safe and precise amount of dissolved ozone from the oxygen in the ice machine's water supply; removable electrolytic cell cartridge; LED indicator lights for cartridge replacement and system function. Shall include 1 year parts-only warranty on head unit and 30 days parts-only warranty on replacement cartridge.

	Water Line Connection	3/8" OD push/pull fitting or 3/8" barbed fitting
TER	Water Temperature	4° C to 30° C WRAS approved for cold water use only in UK. (4° C - 23° C)
WATE	Water Quality	Clean, Potable Water Only (recommended hardness ·300 ppm CaCO ₃)
	Water Supply Pressure	min 20 psi max 125 psi min (1.37 bar) max (8.62 bar)
	Water Flow	1.3lpm - 4.9lpm
		0

- Connect EcO₃Ice only to a Cube, not a Flake/Chewblet ice machine
- 2. Connect only one ice machine per EcO_3 /ce device
- 3. Connect EcO_3 lce only to a commercial ice machine, not a household ice maker.
- 4. Do not connect EcO₃Ice to other devices, such as a Beverage or Ice & Water Dispenser.
- 5. ${\rm EcO_3}$ lce does not replace mechanical water filtration. For best results, always connect ${\rm EcO_3}$ lce in the water supply line between the filtration system and the ice machine.

