

Undercounter and Freestanding Integrated Icemaker with Drain Pump

425 series for foodservice applications

Features

Integrated ice machine with bin, now available with drain pump. Up to 193 kg of production and 36 kg of storage capacity. Perfect for space limited facilities when sewerage installations don't allow to use standard gravity drainage. Less than 61.0 cm wide, the integrated icemaker will provide the capacity you need in a small footprint.

Undercounter application without the legs: 83.8 cm tall unit will fit under standard counters. Teflon glides allow it to slide easily into place. Freestanding: 99.1 cm tall with legs.

Consumer-preferred Micro Chewblet™ ice (also available as a flaker)

- preferred over cubes by more than 2:11
- · easy to chew
- · slow melting, maintains drink temperature and quality, comparable to cubes
- · higher displacement than cube ice

Flake ice is perfect for display

- securely supports salad bar containers without tipping
- · cradles fish and vegetables without bruising

High performance ice machines

- stainless steel evaporator, auger and top bearing provides durability
- · oversized, heavy duty, tapered roller bearing ensures long lowmaintenance life
- semi-automatic cleaning cycle reduces maintenance costs
- regular flushing improves ice quality and reduces scale

Lower utility bills

- · energy-efficient, no costly defrost cycles
- 25% less energy than comparable capacity cube machines
- 40% less water than comparable capacity cube machines


Designed for easy installation and service

- Integrated drain pump gives possibility to install device in place where draining installation is not available. Device can pump the waste water away up to 1.5m vertically and 5m horizontally
- Front ventilated no side, top or back clearance required rear utility access allows for rear electrical and plumbing connection with no rear clearance required
- Bin and shroud may be removed for service and maintenance

Warranty

3 years parts and labor, 5 years compressor parts

Warranty is valid only when periodic maintenance and cleaning instructions is followed.



[†] ENERGY STAR® certified

Model ships EXW Incoterms 2010 – Wislina, Poland. Models not for use in the



Ice machine bin for foodservice

Ice machine bin for foodservice

Coast Distributors Pty Ltd Ph: (02) 9524 1234 / 1800 688 590 PO Box 288, Unanderra, NSW 2526 sales@coastdistributors.com.au www.coastdistributors.com.au







Specification 34 kg Ice storage capacity 59.7 cm W1 Width 66.0 cm D1 Depth H1 Height with legs 99.0 cm 83.8 cm **H2** Height without legs front ventilated - no Service and ventilation clearance side, top or back clearance required Utility connection location 3.8 amps, cord only C1 Electrical 230 V/60/1 5.1 amps, cord only C1 Electrical 230 V/50/1 3/8" push in C2 Potable water inlet C3 Drain 3/8" push in 10 - 38 °C Air temperature 4 - 32 °C Water temperature 10 - 70 psi (69 - 483kpa) Potable water pressure 0.7 Bar - 5 Bar max 193 kg Ice production at 21 C air and 10 C water 147 kg Ice production at 32 C air and 21 C Energy consumption 32 C air; 21 C 5.4 kWh water 5,000 BTU/hr Heat rejection

NOTE: For indoor use only. Designed for commercial use. Follett is not able to provide in-house services for residential installations.

Incoterms is a trademark of the International Chamber of Commerce.

Water consumption

Approximate ship weight

ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Micro Chewblet™ is trademarks of Follett LLC.

45.4 L of potable


84 kg


water per 45.4 kg of

Follett is a registered trademark of Follett LLC, registered in the US.

Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.

Dimensional drawing





Coast Distributors Pty Ltd Ph: (02) 9524 1234 / 1800 688 590 PO Box 288, Unanderra, NSW 2526 sales@coastdistributors.com.au

www.coastdistributors.com.au

